ATLANTIC P60 - P100 – G100

max 330 Bar / 4700 psig

4 stages





BASIC VERSION										
Model	F.A.D. l/min	F.A.D. cfm	Speed rpm	Power kW	Phase	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price EUR
Electric engine										
ATLANTIC P 60/1	60	2,1	2100	1,5	single	ATL	39,5	87,1	58 x 41 x 41	3.800,00
ATLANTIC P 100/1	100	3,5	2100	2,2	single	ATL	42,5	92,6	58 x 41 x 41	3.800,00
ATLANTIC P 100/3	100	3,5	2100	3,0	three	ATL	42	92,6	58 x 41 x 41	3.800,00
Gasoline engine										
ATLANTIC G 100	100	3,5	2100	4,2	-	ATL	42	92,6	77 x 41 x 41	3.965,00

NOTE: Hour meter, maintaining valve and no-return valve on the filter are included as standard features.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi
- Connection type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE).
  Length of all filling hoses = 1meter
- Operating voltage (electric version single phase) Volt/Hz : 230/50 – 230/60
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN	€ 47,00
Filling hose holder	€ 32,50
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 293,00
Double pressure with safety valve(2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 293,00
Double pressure with pressure reducer (2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 1.037,00
Final pressure switch with automatic-stop	€ 285,00
Trolley (2 wheels and handle)	€ 293,00
Folding trolley (2 wheels and reclining handle)	€ 841,00
Automatic condensate drain ATLANTIC P (For electric model with single phase motors)	€ 407,00
Automatic condensate drain ATLANTIC G (For Gasoline model and electric 3-phase model)	€ 537,00
Double purification system	€ 660,00
Eco-friendly Condensate Collecting Container/Tank 5L.	€ 130,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

ATLANTIC D100

max 330 Bar / 4700 psig





BASIC VERSION										
Model	F.A.D.* l/min	F.A.D.* cfm	Speed rpm	Power kW	Phase	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price **EUR**
Diesel engine										
ATLANTIC D 100	100	3,5	2100	3,5	-	ATL	61	135	82 x 37 x 50	6.500,00

NOTE: Hour meter, maintaining valve and no-return valve on the filter are included as standard features.

* Filling rate for 10 liter cylinder capacity from 0 to 200 bar ±5%

** According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi(1) or 330 bar/4700 psi
- Connection type only for 225 bar/3200 psi : DIN(1) or INT (YOKE) or DIN with reduction INT (YOKE). All filling hoses in length of 1 m.

(1) In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN	€ 47,00
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 293,00
Double pressure with safety valve(2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 293,00
Double pressure with pressure reducer (2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 1.037,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC E - EG

max 330 Bar / 4700 psig





BASIC VERSION											
Model	F.A.D. l/min	F.A.D. cfm	Nr. of stages	Speed rpm	Power kW	Phase	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price **EUR**
Electric motor											
PACIFIC E 16 * *(not available with Control Panel)*	160	5,6	3	1350	3,0	single	PAC 1	108	238	103 x 53 x 65	8.345,00
PACIFIC E 23 *	230	8,1	3	1350	4,0	three	PAC 1	108	238	103 x 53 x 65	8.425,00
PACIFIC E 27 *	270	9,5	3	1550	5,5	three	PAC 1	118	260	103 x 53 x 65	9.220,00
PACIFIC E 30	300	10,6	3	1450	5,5	three	PAC 1	118	260	103 x 53 x 65	10.255,00
PACIFIC E 35	350	12,4	4	1550	7,5	three	PAC 1	123	277	103 x 53 x 65	12.275,00
Gasoline engine											
PACIFIC EG 23 *	230	8,1	3	1350	6,7	-	PAC 1	108	238	111 x 53 x 65	9.410,00
PACIFIC EG 27 *	270	9,5	3	1550	6,7	-	PAC 1	108	238	111 x 53 x 65	10.670,00
PACIFIC EG 30	300	10,6	3	1450	10	-	PAC 1	118	260	111 x 53 x 65	11.795,00
PACIFIC EG 35	350	12,4	4	1550	10	-	PAC 1	123	277	111 x 53 x 65	14.390,00

* With splash lubrication , Oil pump is optional

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with 2 filling devices)
  Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version single phase) Volt/Hz : 230/50[1] - 230/60
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price /EUR
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Automatic System for Electric models (Elect. Control Panel and Automatic Condensate Drain)	€ 2.470,00
Soft Start (available for PACIFIC E with charging rate 230 lpm, 270 lpm, 300 lpm and 350 lpm)	€ 1.400,00
Oil Alert	€ 260,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Hour Meter (Only for Gasoline models and electrical with manual controls)	€ 178,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psiand 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Filling device 4-fold (supplied with 2 filling connections and 2 plugs either at DIN 200, 225bar/3200psi or DIN 300, 330bar/4700psi)	€ 275,00
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Trolley (2 wheels and handle)	€ 455,00
Handles (Set of 2)	€ 252,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 130,00
Large separators	€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC P - PG

max 330 Bar / 4700 psig





BASIC VERSION											
Model	F.A.D. l/min	F.A.D. cfm	Nr. of stages	Speed rpm	Power kW	Phase	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price EUR
Electric motor											
PACIFIC P 16 *	160	5,6	3	1350	3,0	single	PAC 1	127	300	120 x 54 x 67	9.285,00
PACIFIC P 23 *	230	8,1	3	1350	4,0	three	PAC 1	127	300	120 x 54 x 67	9.285,00
PACIFIC P 27 *	270	9,5	3	1550	5,5	three	PAC 1	137	302	120 x 54 x 67	10.325,00
PACIFIC P 30	300	10,6	3	1450	5,5	three	PAC 1	137	302	120 x 54 x 67	11.490,00
PACIFIC P 35	350	12,4	4	1550	7,5	three	PAC 1	142	313	120 x 54 x 67	13.375,00
Gasoline engine											
PACIFIC PG 23 *	230	8,1	3	1350	6,7	-	PAC 1	113	249	120 x 54 x 67	10.775,00
PACIFIC PG 27 *	270	9,5	3	1550	6,7	-	PAC 1	113	249	120 x 54 x 67	11.325,00
PACIFIC PG 30	300	10,6	3	1450	10	-	PAC 1	123	271	120 x 54 x 67	12.515,00
PACIFIC PG 35	350	12,4	4	1550	10	-	PAC 1	128	282	120 x 54 x 67	14.985,00

* With splash lubrication , Oil pump is optional

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version single phase) Volt/Hz : 230/50[(1)] - 230/60
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price/EUR
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Automatic System for Electric models (Elect. Control Panel and Automatic Condensate Drain)	€ 2.360,00
Automatic System for Gasoline models (Auto. Cond. Drain, Autostop, Electric Start with Key)	€ 2.275,00
Soft Start (available for PACIFIC P with charging rate 230 lpm, 270 lpm, 300 lpm and 350 lpm)	€ 1.400,00
Oil Alert	€ 260,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Hour Meter (Only for Gasoline models and electrical with manual controls)	€ 178,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psiand 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Trolley (2 wheels and handle)	€ 455,00
Handles (Set of 2)	€ 252,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC DY

max 330 Bar / 4700 psig



BASIC VERSION											
Model	F.A.D. l/min	F.A.D. cfm	Nr. of stages	Speed Rpm	Power kW	Engine	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price EUR
Diesel Engine											
PACIFIC DY 23 *	230	8,1	3	1350	7,4	Yanmar	PAC 1	165	364	109 x 58 x 65	15.405,00
PACIFIC DY 27 *	270	9,5	3	1550	7,4	Yanmar	PAC 1	165	364	109 x 58 x 65	16.215,00
PACIFIC DY 30	300	10,6	3	1450	7,4	Yanmar	PAC 1	172	379	109 x 58 x 65	17.340,00
PACIFIC DY 35	320	12,7	4	1350	7,4	Yanmar	PAC 2	172	379	109 x 58 x 65	18.200,00

* With splash lubrication , Oil pump is optional.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price/EUR
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Automatic System (Auto. Cond. Drain, Autostop, Electric Start with Key)	€ 2.275,00
Oil Alert	€ 260,00
Hour meter	€ 178,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Additional hose connections (for a maximum of 2 hose connections with pressure gauge: 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Trolley (2 wheels and handle)	€ 455,00
Handles (Set of 2)	€ 252,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC C

max 330 Bar / 4700 psig



BASIC VERSION											
Model	F.A.D. l/min	F.A.D. cfm	Nr. of stages	Speed Rpm	Power kW	Phase	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price **EUR**
Electric motor											
PACIFIC C 16 *	160	5,6	3	1350	3,0	single	PAC 1	234	516	75 x 93 x 123	12.595,00
PACIFIC C 23 *	230	8,1	3	1350	4,0	three	PAC 1	234	516	75 x 93 x 123	12.780,00
PACIFIC C 27 *	270	9,5	3	1550	5,5	three	PAC 1	239	527	75 x 93 x 123	13.060,00
PACIFIC C 30	300	10,6	3	1450	5,5	three	PAC 1	239	527	75 x 93 x 123	14.170,00
PACIFIC C 35	350	12,4	4	1550	7,5	three	PAC 2	247	545	75 x 93 x 123	16.440,00

*With splash lubrication , Oil pump is optional.

Oil alert is available as a standard feature.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 2-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50[(1)] - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Soft Start (available for PACIFIC C with charging rate 230 lpm, 270 lpm, 300 lpm and 350 lpm)	€ 1.400,00
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure with safety valve (2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 894,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC M

max 330 Bar / 4700 psig



BASIC VERSION											
Model	F.A.D.**		Nr. of	Speed	Power	Phase	Purification	Weight		Dimensions	Price
	l/min	cfm	stages	rpm	kW		system	Kg	lbr	L x W x H	EUR
Electric motor											
PACIFIC M 23 *	230	8,1	3	1350	4,0	three	PAC 1	264	582	75 x 108 x 134	14.140,00
PACIFIC M 27 *	270	9,5	3	1550	5,5	three	PAC 1	269	593	75 x 108 x 134	14.545,00
PACIFIC M 30	300	10,6	3	1450	5,5	three	PAC 1	269	593	75 x 108 x 134	15.590,00
PACIFIC M 35	350	12,4	4	1550	7,5	three	PAC 2	277	674	75 x 108 x 134	18.165,00

* With splash lubrication , Oil pump is optional.

Oil alert is available as a standard feature.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi[(1)] or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN[(1)] or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50[(1)] - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Soft Start	€ 1.400,00
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Additional hose connections (for a maximum of 2 hose connections with pressure gauge: 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00
Atex Certificate Zone II	€ 4.875,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC M NITROX

max 330 Bar / 4700 psig

4 stages



BASIC VERSION										
Model	F.A.D. l/min	F.A.D. cfm	Speed rpm	Power kW	Pump unit	Purification system	Weight Kg	Weight lbr	Dimensions L x W x H	Price EUR
Electric motor										
PACIFIC M NITROX 30	300	10,6	1300	5,5	PAC35	PAC 2	277	674	75 x 108 x 134	19.980,00

Pressure and Temperature Sensors on all stages are a standard feature.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Soft Start	€ 1.400,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Additional hose connections (for a maximum of 2 hose connections with pressure gauge: 225bar/3200 or 330bar/4700psi)	€ 290,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC CX

max 330 Bar / 4700 psig



BASIC VERSION											
Model	F.A.D.** l/min	F.A.D.** m3/h	Nr. of stages	Speed rpm	Power kW	Phase	Purification System	Weight Kg	Weight lbr	Dimensions L x W x H	Price **EUR**
PACIFIC CX Silenced Version											
PACIFIC CX 50	500	30	3	1100	11	three	PAC 3	400	882	84x75x142	18.700,00
PACIFIC CX 60	600	36	3	1300	11	three	Double PAC3	420	926	84x75x142	21.150,00
PACIFIC CX 68	680	42	4	1100	15	three	Double PAC3	470	1036	84x75x142	26.400,00
PACIFIC CX 85	850	51	4	1300	18.5	three	Double PAC3	570	1256	84x75x142	29.400,00

Soft Start, Oil Pump, Oil Alert and Large separators are available as standard features on all PACIFIC CX compressors.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 4 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric motor three phase) Volt/Hz : 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

(1) In case this information is not provided, the price will be calculated with standard configuration

(2) All compressors of PACIFIC CX range are equipped with four n. 4 filling hoses and Eco-friendly condensate collecting Container 12 Lt.

OPTIONAL EQUIPMENT	Price EUR
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Supplementary Filtering System (2 x PAC Filter 3) Upgrade from single PAC Filter 3 for CX 50 and CX 60	€ 1.950,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 2 filling hoses DIN 200 bar and 2 filling hoses DIN 300 bar)	€ 894,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Atex Certificate Zone II	€ 4.875,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).

PACIFIC MX

max 330 Bar / 4700 psig



BASIC VERSION											
Model	F.A.D.** l/min	F.A.D.** m3/h	Nr. of stages	Speed rpm	Power kW	Phase	Purification System	Weight Kg	Weight lbr	Dimensions L x W x H	Price **EUR**
PACIFIC MX Silenced Version											
PACIFIC MX 50	500	30	3	1100	11	three	PAC 3	460	1014	87x156x173	20.550,00
PACIFIC MX 60	600	36	3	1300	11	three	Double PAC3	500	1102	87x156x173	22.900,00
PACIFIC MX 60/4	600	36	4	950	11	three	Double PAC3	520	1146	87x156x173	27.300,00
PACIFIC MX 68	680	42	4	1100	15	three	Double PAC3	520	1146	87x156x173	28.100,00
PACIFIC MX 85	850	51	4	1300	18.5	three	Double PAC3	620	1367	87x156x173	31.050,00

Soft Start, Oil Pump, Oil Alert and Large separators are available as standard features on all PACIFIC MX compressors.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 4 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric motor three phase) Volt/Hz : 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

(3) In case this information is not provided, the price will be calculated with standard configuration

(4) All compressors of PACIFIC MX range are equipped with four n. 4 filling hoses and Eco-friendly condensate collecting Container 12 Lt.

OPTIONAL EQUIPMENT	Price EUR
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Supplementary Filtering System (2 x PAC Filter 3) Upgrade from single PAC Filter 3 for MX 50 and MX 60	€ 1.950,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 2 filling hoses DIN 200 bar and 2 filling hoses DIN 300 bar)	€ 894,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Atex Certificate Zone II	€ 4.875,00

PACIFIC MX NITROX

max 330 Bar / 4700 psig

4 stages



BASIC VERSION										
Model *	F.A.D.** l/min	F.A.D.** m3/h	Speed rpm	Power kW	Pump unit	Purification System	Weight Kg	Weight lbr	Dimensions L x W x H	Price EUR
PACIFIC MX NITROX Silenced Version										
PACIFIC MX 60N	600	36	950	11	MX 60	2 x PAC 3	520	1146	87 x 156 x 173	29.100,00

Soft Start, Oil Pump, Oil Alert, Large separators and Temperature and Pressure Sensors on all stages are available as standard features.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi (standard version supplied with filling device 4-fold with 4 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric motor three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

(1) In case this information is not provided, the price will be calculated with standard configuration

(2) All compressors of PACIFIC MX range are equipped with four n. 4 filling hoses and Eco-friendly condensate collecting Container 12 Lt.

OPTIONAL EQUIPMENT	Price EUR
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 2 filling hoses DIN 200 bar and 2 filling hoses DIN 300 bar)	€ 894,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).